

UNITED STATES DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form approved.  
Budget Bureau No. 42-R1424.

FEB 21 1980

SUNDRY NOTICES AND REPORTS ON WELLS

O. C. D. (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

ARTESIA, OFFICE

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* See also space 17 below.)  
At surface

1980' FNL & 1980' FEL of Section 10-7S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3821' GR

5. LEASE DESIGNATION AND SERIAL NO.

USA NM-10893

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Godfery MP Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Granite Wash

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10-7S-25E

Unit G NMPM

12. COUNTY OR PARISH 13. STATE

Chaves

NM

18.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Set Production Csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 4647' - Ran 116 joints of 4½" 9.5# K-55 (4672') of casing set at 4647'. 1-Guide shoe at 4647', 1-float collar at 4597'. Cemented w/50-50 Lite Poz-3 Class C 1/10% D-108, 2/10% D-65, 3#/sack KCL, 10 bbls CW-100 ahead of cement. PD 9:45 AM 1-31-80. WOC and tested to 1000#. OK. Ran temperature survey and found top of cement at 2950'. WLPBTD 4609'.

18. I hereby certify that the foregoing is true and correct

SIGNED

*George H. Stewart*

TITLE

Geol. Secty.

DATE

2-14-80

(This space for Federal or State office use)

(Sgd.) GEORGE H. STEWART

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*WILLIAM D. BROWN*

DATE

FEB 20 1980