

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-70

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

DEC 31 1980

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Fred Pool Drilling, Inc.		8. Farm or Lease Name Corn Bros. Inc.
3. Address of Operator 1300 Clovis Star Rt. Roswell, New Mexico		9. Well No. #1
4. Location of Well UNIT LETTER B 1980 FEET FROM THE E LINE AND 660 FEET FROM THE N LINE, SECTION 19 TOWNSHIP 6s RANGE 25e NMPM.		10. Field and Pool, or Wildcat Wildcat Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3856.22 GR		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Perforating and Acidizing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-9-80

Perforated 3658 - 3666 1 per foot.

3727 - 3730

3734 - 3744

Set bridgeplug at 3700'. Set packer at 3610'.

Acidized with 35,000 gals. foam and 42,000 lbs sand at
3658 - 3666.

Preparing to put on lump.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Penny K. Martin TITLE Secretary DATE 12-30-80

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE JAN 02 1981

CONDITIONS OF APPROVAL, IF ANY: