

RECEIVED

Form 9-331
(May 1963)

FEB 21 1980

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM- 11103

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Globe MN Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Al

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1-5S-24E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3896' GR

12. COUNTY OR PARISH

Chaves

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud, 5½" Prod. Csg.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 17½" hole at 6:00 PM 1-30-80.

TD 357' - Ran 10 joints of 13-3/8" 48# K-55 (357') of casing set at 357'. 1-Guide Shoe at 357'. Cemented w/350 sacks Class C 4% CaCl. Slurry wt. 14.8, 1.32 cu ft/sx. Compressive Strength at 70 degrees 1023 psi in 12 hours. PD 7:00 AM 1-31-80. Cement circulated 10 sacks to surface. WOC 12 hours, backed off and reduced hole to 12¼" drilled plug and tested to 600# OK and resumed drilling.

TD 4260' - Ran 100 joints of 5½" J-55 14# ST&C (4028') of casing set at 4026'. 1-Regular Pattern Guide shoe at 4026'. Diff-fill collar at 3986'. 5-centralizers at 3986, 3786, 3666, 3546, 3426'. Cemented w/185 sacks 50-50 Poz w/3# KCL, 1/10% D-108, 2/10% D-66. Tailed in w/80 sacks Class C Neat. PD 5:02 AM 2-11-80. WOC and tested to 1000# OK. Ran Temperature Survey and found top of cement at 2930'.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine L. Jensen

TITLE

Geol. Secty

DATE

2-14-80

(This space for Federal or State office use)

(Eng. Sgd.) GEORGE H. STEWART

APPROVED BY

TITLE

DATE

FEB 21 1980

CONDITIONS OF APPROVAL, IF ANY: