16.

N.M.O.C.D. COPY

ITED STATES SUBMIT IN T. JCATE* Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

NM-28152	MECEINED.
A	TAN BRIDE OF WALL

GEOLOGICAL SURVE		AND OD MRIDE NAME	
SUNDRY NOTICES AND REPOR (Do not use this form for proposals to drill or to deepen or Use "APPLICATION FOR PERMIT—" for	IS ON THE ELVED plug back to a dinerese reservoir. ED such proposals.)		1 2 7 1990
OIL GAS WELL OTHER	JUN 2 5 1980		SIA OFFICE
2. NAME OF OPERATOR Yates Petroleum Corporation	U.S. GEULUGICAL SURVE ARTESIA, NEW MEXICO		
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia	IM 88210	10. FIELD AND POOL,	
4. LOCATION OF WELL (Report location clearly and in accordance wis See also space 17 below.) At surface 1780' FNL & 560' FEL of Section		Wildcat 11. SEC., T., E., M., O SURFWIT OR AR Sec. 34-6S Unit H	DR BLK. AND ABA 5 -24E NMPM
14. PERMIT NO. 15. ELEVATIONS (Show wh	ther DF, RT, GR, etc.) GR	12. COUNTY OF PART	ISH 13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF	INTENTION TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
(Other)		the land size portinent dates, including estimated date of starting at

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 5523' - Ran 121 joints of $5\frac{1}{2}$ " 14# K-55 (5040') of casing set at 5040'. 1-guide shoe at 5040' and float collar at 5000'. Cemented w/750 sacks 50-50 Poz C 4% gel, 4/10% Halad-22, 2/10% CFR-2, 5# KCL. PD 12:30 PM 3-6-80. WOC and ran Temperature Survey and found top of cement at 3210'. WLPBTD 5026'. Tested to 1500# OK.

18. I hereby certify that the foregoing is true and correct SIGNED	Geol. Secty.	DATE	6-24-80
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	ACTURE OF COLUMN FOR COLUMN A	DATE	104 5 0 1377 —