

## L CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fed <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS MAR 28 1980

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	O. C. D. ARTESIA OFFICE	7. Unit Agreement Name
2. Name of Operator Stevens Oil Company		8. Farm or Lease Name O'Brien "F"
3. Address of Operator P. O. Box 2203, Roswell, New Mexico 88201		9. Well No. 4
4. Location of Well UNIT LETTER <u>K</u> , <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>8-S</u> RANGE <u>28-E</u> NMPM.	10. Field and Pool, or Wildcat Assoc. Twin Lakes-San Andres	
15. Elevation (Show whether DF, RT, GR, etc.) 3920.3 Gr., 3926.3 KB	12. County Chaves	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-02-80 Staked Location.  
3-03-80 Moving in Rig.  
3-04-80 Spudded. Drilled 120' and ran 120' 8-5/8" <sup>20#</sup> surface casing, cemented with 75 sacks Class "C" cement 2% calcium chloride. WOC 24 hrs.  
3-09-80 Ran 2770' 4-1/2" 9.5# surface casing and cemented with 50 sacks Class C cement and 75 sacks self-stress cement. WOC  
3-19-80 Perf. 2566, 66.5, 68.5, 69, 69.5, 70, 71.5, 72, 78, 78.5, 79, 79.5, 81, 81.5, 82.5, 83, 94, 94.5, 96, 96.5, 97, 97.5 Acidized perfs. with 6000 gal. 28% acid with ball sealers. Testing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald G. Stein TITLE Owner DATE 3-25-80APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: