

L CONSERVATION DIVISIO
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

5a. Indicate Type of Lease
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Stevens Oil Company	8. Farm or Lease Name O'Brien "F"
3. Address of Operator P. O. Box 2203, Roswell, New Mexico 88201	9. Well No. 4
4. Location of Well UNIT LETTER <u>K</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>8-S</u> RANGE <u>28-E</u> NMPM.	10. Field and Pool, or Wildcat Und. Twin Lakes-San Andres Assoc.
11. Elevation (Show whether DF, RT, GR, etc.) 3920.3 Gr., 3926.3 KB	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-02-80 Staked Location.
3-03-80 Moving in Rig.
3-04-80 Spudded. Drilled 120' and ran 120' 8-5/8 " 20# surface casing, cemented with 75 sacks Class "C" cement 2% calcium Chloride. WOC 18 hours. Pressured to 1000#/30 minutes. Logging no pressure decrease.
3-09-80 Ran 2770' 4-1/2" 9.5# surface casing and cemented with 50 sacks Class C cement and 75 sacks self-stress cement. WOC 18 hours. Pressured to 1000#/30 minutes. Logging no pressure decrease.
3-19-80 Perf. 2566, 66.5, 68.5, 69, 69.5, 70, 71.5, 72, 78, 78.5, 79, 79.5, 81, 81.5, 82.5, 83, 94, 94.5, 96, 96.5, 97, 97.5. Acidized perfs. with 6000 gal. 28% acid with ball sealers. Testing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald E. Atten TITLE Owner DATE 3-25-80
APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE APR 1 1980

CONDITIONS OF APPROVAL, IF ANY: