

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.B.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

OCT 31 1980

O. C. C.

ARTESIA, COLORADO

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Coronado Exploration Corp. /	8. Farm or Lease Name Sarah
3. Address of Operator 1005 Marquette NW Albuquerque, NM 87102	9. Well No. 1
4. Location of Well UNIT LETTER 0 1980 FEET FROM THE East LINE AND 660 FEET FROM THE South LINE, SECTION 15 TOWNSHIP 10S RANGE 27E NMPM.	10. Field and Pool, or Wildcat Und. Diablo SA
15. Elevation (Show whether DF, RT, GR, etc.) 3806.9	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 8 5/8" @ 250'

We propose to plug the subject well as follows:

Cut and pull as much casing (4 1/2") as possible

1st plug - 30 sx Dowell Class "C" w/2% CaCl below top of Slaughter, 2122'-2000'

2nd plug - 35 sx Dowell Class "C" w/2% CaCl to cover San Andres - 1628'-1528'

4th ~~3rd~~ plug - 35 sx Dowell Class "C" w/2% CaCl to cover Queen - 1000-900'

3rd ~~4th~~ plug - 35 sx Dowell Class "C" w/2% CaCl centered over stub of 4 1/2" cs 3. (Approx. 1100') + 29

5th plug - 35 sx Dowell Class "C" w/4% CaCl, 300'-200' + Tag

6th plug - 10 sx Dowell Class "C" w/4% CaCl, to surface.

Spaces between plugs will be filled with mud spacer

Location will be cleaned and pits leveled. We will notify you when pads are ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CORONADO EXPLORATION CORP.

SIGNED Gail Gunnels TITLE Production Secretary DATE October 29, 1980

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE NOV 05 1980

CONDITIONS OF APPROVAL, IF ANY: As Noted Above Notify N.M.O.C.C. in sufficient time to witness Plugging