

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDY NOTICES AND REPORTS ON WELLS **APR 5 1980**
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	O. C. D. ARTESIA, OFFICE	7. Unit Agreement Name
2. Name of Operator Coronado Exploration Corp.		8. Firm or Lease Name Whitney
3. Address of Operator 1005 Marquette NW Albuquerque, NM 87102		9. Well No. 1
4. Location of Well UNIT LETTER <u>I</u> <u>1980</u> FEET FROM THE <u>south</u> LINE AND <u>660</u> FEET FROM THE <u>east</u> LINE, SECTION <u>34</u> TOWNSHIP <u>10S</u> RANGE <u>27E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether LF, RT, GR, etc.) 3775.8 Gr		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 412' of 8-5/8" 20# casing. Cemented with 200 sx Dowell Class C cement with 2% CaCl. Cement circulated to surface. WOC 18 hrs. Bailed hole dry, waited 1 hour and found no water in casing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CORONADO EXPLORATION CORP.

BY: [Signature]

SIGNED _____

TITLE ENGINEER

DATE APRIL 23, 1980

APPROVED BY [Signature]

TITLE SUPERVISOR, DISTRICT II

DATE APR 29 1980

CONDITIONS OF APPROVAL, IF ANY: