

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	1	
FILE	1	
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

MEXICO OIL CONSERVATION COMMISSION

RECEIVED

MAY 12 1980

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS O. C. D. (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - "A" (FORM C-101) FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☒ Fee ☐
1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-		5. State Oil & Gas Lease No. LG-4898
2. Name of Operator Yates Petroleum Corporation		7. Unit Agreement Name
3. Address of Operator 207 South 4th Street - Artesia, NM 88210		8. Farm or Lease Name Nine Mile "LV" St. Com
4. Location of Well UNIT LETTER <u>I</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>14S</u> RANGE <u>28E</u> NMPL.		9. Well No. <u>1</u>
15. Elevation (Show whether DF, RT, GR, etc.) 3531' GR		10. Field and Pool, or Wildcat Unds Buffalo Valley Penn
		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17½" hole at 8:15 AM 4-22-80.

TD 312' - Ran 8 joints of 13-3/8" 54.5# H-40 ST&C (316') of casing set at 312'. 1-Texas Pattern guide shoe at 312' and insert float at 272'. Cemented w/325 sacks of Class C 4% CaCl. Slurry wt. 14.8, 1.32 cu ft/sack. Compressive strength at 70 degrees 1023 psi in 12 hours. PD 5:15 PM 4-22-80. Circulated 45 sacks of cement to surface. WOC 12 hours, reduced hole to 12¼", drilled plug, tested to 600# OK and resumed drilling.

TD 1728'- Ran 43 joints of 8-5/8" 24# K-55 8R (1731') of casing set at 1728'. 1-Guide shoe at 1728', flapper insert at 1681'. Cemented w/900 sacks 65-35 Poz, 8# Kolite/sx, 1/4# celloflakes/sx, 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 4:00 PM 4-24-80. Circulated 25 sacks to pit. WOC 18, NU, reduced hole to 7-7/8", drilled plug, tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty. DATE 5-10-80

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAY 13 1980

CONDITIONS OF APPROVAL, IF ANY: