

DISTRIBUTION		
SANTA FE	1	
FILE	1	
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED

APR 28 1980

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th Street - Artesia, NM, 88210

4. Location of Well
UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 2 TOWNSHIP 5S RANGE 24E NMPM.

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
LG 563

7. Unit Agreement Name

8. Farm or Lease Name
Smernoff "NL" State

9. Well No.
1

10. Field and Pool, or Wildcat
~~Wildcat~~ Abo

12. County
Chaves

15. Elevation (Show whether DF, RT, GR, etc.)
3974' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 9:00 PM 4-5-80.

TD 400'- Ran 10 joints of 10-3/4" 33# ST&C (400') of casing set at 400'. 1-Texas Pattern guide shoe at 400' and insert float at 360'. Cemented w/375 sacks of Class C 4% cacl. PD 9:55 AM 4-6-80. Cement circulated 35 sacks to surface. WOC 12 hours, backed off, reduced hole to 7-7/8", drilled plug and tested to 600# OK. Resumed drilling.

TD 4276'- Ran 98 joints of 5 1/2" 14# J-55 ST&C (4135') of casing set at 4135'. 1-Guide shoe at 4135' and insert float at 4049'. 5-centralizers at 3935, 3815, 3695, 3575 and 3455'. Cemented w/400 sacks of 50-50 Poz, 3#/sx KCL, 3/10% D-108, 2/10% D-65. Tailed in w/100 sacks of Class C 2% CaCl. PD 2:20 AM. WOC. Tested to 1000# OK. Top of cement at 2530'.

TD 4276'; PBTD 4135' - WIH w/Steel Strip gun on wireline & perforated 3630-3662' w/44 .50" holes as follows: 3630-38 (8holes); 3648-62' (14 holes)(Total 22 holes (2spf). WIH w/Guiberson Uni VI packer on 2-7/8" tubing, set packer at 3592'. Acidized w/3000 gallons 15% Spearhead acid w/ball sealers. Sand Frac'd w/21126 gal. Titan II-30 KCL gel & 50000# sand (10000# 100 mesh & 40000# 20-40 sand) w/ball sealers and CO-2.

I, hereby certify that the information above is true and complete to the best of my knowledge and belief.

CREATED Christine Tomlinson TITLE Geol. Secty. DATE 4-28-80

PROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II DATE MAY 13 1980

CONDITIONS OF APPROVAL, IF ANY: