

United States Department of the Interior

GEOLOGICAL SURVEY
P. O. Drawer U
Artesia, New Mexico 88210

MAR 4 1980

O. C. D. ARTESIA, OFFICE

February 29, 1980

3515515

McClellan Oil Corporation
P. O. Drawer 730
Roswell, New Mexico 88201

Gentlemen:

McCLELLAN OIL CORPORATION
"PJ" Fed No. 1
1980 FSL 1980 FEL Sec. 6 T.9S R.26E
Chaves County Lease No. NM 11596

Above Data Required on Well Sign

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 4,700 feet to test the Abo formation is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

- Drilling operations authorized are subject to compliance with the GENERAL REQUIREMENTS FOR OIL AND GAS OPERATIONS ON FEDERAL LEASES, dated July 1, 1978.
- 2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the SURFACE USE PLAN and this approval including the GENERAL REQUIREMENTS.
- 3. All access roads will be limited to a 12 foot wide driving surface, excluding turnarounds. Surface disturbance associated with road construction will be limited to 20 feet in width.
- 4. Submit a Daily Report of Operations from spud date until the Well Completion Report (form 9-330) is filed. The progress report should be not less than 8" x 5" in size and each page should identify the well.
- 5. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Requirements. The color used should simulate Sandstone Brown (Federal Standard No. 595A, color 20318 or 30318).
- 6. Notify the Survey by telephone 24 hours prior to spudding well.
- 7. Cement behind the 8-5/8" casing must be circulated.

