Form 9–331	LINITED STATES				Form Approved. Budget Bureau No. 42–R1424			
	TED STATES IT OF THE INTERIOR		5.	LEASE NM - 3	6643			
	GICAL SURVEY	•	6.	IF INDIAN, A			AME	
SUNDRY NOTICES	AND REPORTS O	N WELLS	7.	UNIT AGREE	MENT NAM	E	-	
(Do not use this form for proposals reservoir, Use Form 9–331–C for suc	ch proposals.)		8.	FARM OR LE		AUS	S 5 198	
1. oil gas well X	other	-	9.	ROCK FE WELL NO.	DERAL			
2. NAME OF OPERATOR	,			4		7.37		
MESA PETROLEUM CO			10.	FIELD OR WI	ILDCAT NAM GNATED A		٠.	
3. ADDRESS OF OPERATOR 1000 VAUGHN BUILD	ING/MIDLAND, TEXA	AS 79701	11.	SEC., T., R.,			RVEY OR	
4. LOCATION OF WELL (RE	PORT LOCATION CLEARL	Y. See space 17			c 6 , T8S	, R23E	2	
AT SURFACE: 660' AT TOP PROD. INTERVA	FNL & 1980' FWL L:		12.	COUNTY OR CHAVES	PARISH 1		MEXICO	
AT TOTAL DEPTH:	,	DE OF NOTICE	14.	API NO.				
16. CHECK APPROPRIATE B REPORT, OR OTHER DA	OX TO INDICATE NATU TA	RE OF NOTICE,	15.	ELEVATION:		F, KDB, A	ND WD)	
REQUEST FOR APPROVAL TO TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	O: SUBSEQUENT	PEPORT OF:	104	Bot E: Report re	7	ple complet	on or zone	
REPAIR WELL PULL OR ALTER CASING [MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Spud 8	5/8" csg & cement	US GEOLOGIA	1145	change o	on Form 9–33	2.) ₁₃		
	of starting any proposed	ONS (Clearly state	all	pertinent de onally drilled	tails, and g , give subsu	ive pertino irface loca	ent dates itions and	

17. DESCR measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded well with 12 1/4" hole on 8-13-81. Hit FW at 100' - TSTM. Drilled to 1449' without returns. Ran 37 jts 8-5/8", 24#, K55 casing set at 1440'. Cemented with 800 sx HLW + 1# flocele + 4% ČaCl, 300 sx Thixset + 4% CaCl, and tailed in with 200 sx "C" + 2% CaCl. PD at 11:00 a.m. 8-15-81. Cement did no circulate. Ran temp survey - TOC at 700'. Set two plugs with total of 300 sx Thixset + 4% CaCl. Circulated 10 sx. Reduced hole to 7-7/8", tested BOPs and casing to 600 psi for 30 min- OK, and drilled ahead on 8-16-81. WOC total of 21 hours. NOTE: Cement job witnessed by B. Jones/ USGS.

XC: USGS (3), TLS, CEN RCDS Subsurface Safety Valve: Manu. and Type	s, ACCTG, MEC, LAND, 1	PARTNERS,	ROSWELL FILE	Ft.
18. I hereby certify that the foregoing is tr				
SIGNED RECORD	TIREGULATORY COORD	INATOBATE _	8-17-81	
ROSER A. CHAPMAN	(This space for Federal or State offi	ice use)		
APPROVED BY	TITLE	DATE _		
CONDITIONS OF AAH GVAL 4 1981			•	
U.S. GEOLÓGICAL SURVEY ROSWELL, NEW MEXICO		Elda		•