

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501
MAY 22 1980

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

3a. Indicate Type of Lease
State ☒ Fee ☐
3. State Oil & Gas Lease No.
L-4606

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL ☐ GAS ☒ OTHER ☐	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Form or Lease Name Sink Hole NR St. Com
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> 1980 FEET FROM THE <u>North</u> LINE AND 1980 FEET FROM THE <u>East</u> LINE, SECTION <u>8</u> TOWNSHIP <u>10S</u> RANGE <u>26E</u> N10PM	10. Field and Pool, or Wildcat Wildcat Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3800 GR	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOBS ☒	OTHER ☒ Set Production Casing

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 1:00 AM 5-6-80.

TD 926' - Ran 22 joints of 8-5/8" 24# J-55 (928') of casing set at 926' KB. 1-Texas Pattern guide shoe at 926' and insert float at 885'. Cemented w/450 sacks 65-35 Poz, 4% D-20, 1/4# D-29, 8# D-42, 3% S-1. Tailed in w/150 sacks Class C 2% S-1. PD 9:00 PM 5-7-80. Cement circulated 30 sacks to surface. WOC 18 hours Nipples up and tested to 1000# OK, reduced hole to 7-7/8", drilled plug and tested to 600# OK. Resumed drilling. TD 5200'. Ran 117 joints of 5 1/2" 14# K-55 (4936') of casing set at 4936'. 1-Texas Pattern guide shoe at 4936' and Diff-Fill float at 4894'. 6-Centralizers. Cemented w/450 sacks of 50-50 Poz, 2/10% D-65, 3# M-117, 1/2# O-46. PD 3:00 5-21-80. WOC and tested to 1500# OK. Ran Temperature Survey and found top of cement at 3360'. WLPBTD 4890'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine Imbriano</u>	TITLE <u>Geol. Secty.</u>	DATE <u>5-21-80</u>
APPROVED BY <u>W.A. Gussitt</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>MAY 23 1980</u>

CONDITIONS OF APPROVAL, IF ANY:

CLIFFARD



BENNETT WIRE LINE SERVICE

P. O. BOX 787
ARTESIA, NEW MEXICO 88210
Phone 746-3281



TEMPERATURE SURVEY

OPERATOR YATES PETROLEUM CORP

LEASE SINK HOLE 8-10-24

WELL NO. #1

FIELD NO. _____

DATE & TIME CEMENT JOB COMPLETED 5-21-80 0300 HOURS

DATE & TIME SURVEY MADE 5-21-80 1200 HOURS

SURVEY RUN BY E.D. BENNETT

DATUM _____

WELL DATA TOTAL DEPTH 4,890 FEET

CEMENT TOP 3,360 FEET

RECEIVED

JUN 20 1980

O. C. D.
ARTESIA, OFFICE

