

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-60689

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-5650

7. Lease Name or Unit Agreement Name:

Hook AWX State

7. Well No.

#1

8. Pool name or Wildcat

Wildcat Precambrian

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter **G** : **1980** feet from the **North** line and **1980** feet from the **East** line

Section **8** Township **10S** Range **26E** NMPM **Chaves** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3800' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Set production casing, cement ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

12/23/00 - Ran 157 jts. (6587') 5-1/2" 15.5# casing set at 6580'.

Float shoe set at 6580'. Float collar set at 6535.14'.

Bottom marker set at 6180-6202'. Top marker set at 5277-5297'.

Cement as follows: 500 gals mud flush + 1100 sxs Pecos Valley Lite (yld 1.4, wt 13).

12/24/00 - PD at 3:45 AM. Float and casing held.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE August 24, 2001

Type or print name **Susan Herpin**

Telephone No. **505-748-1471**

(This space for State use)

APPROVED BY BH ORIGINAL SIGNED BY TIM W. GUM

DISTRICT II SUPERVISOR TITLE

DATE AUG 27 2001

Conditions of approval, if any: