

Yates Petroleum Corporation
Hook AWX State #1
API 30-005-60689
Section 8 T10S R26E
Chaves County, NM

26. Perforation Record (Interval, Size, and Number)

Ordovician	6250-6274'	96 holes	.41" holes
	6186-6190'	16 holes	.41" holes
	6206-6213'	28 holes	.41" holes
	6220-6224'	16 holes	.41" holes
	6230-6234'	16 holes	.41" holes
Mississippian	5974-5982'	32 holes	.41" holes
	6008-6018'	40 holes	.41" holes
Wolfcamp	5452-5466'	15 holes	.41" holes
	5482-5504'	23 holes	.41" holes
	5518-5548'	31 holes	.41" holes
	5564-5578'	15 holes	.41" holes

27. Acid, Shot, Fracture, Cement, Squeeze, etc.

Depth Interval	Amount and Kind Material Used
6250-6274'	Spot 50 gals 20% IC HCL
	Acidize with 200 gals 20% IC HCL
	Acidize with 2400 gals 20% IC HCL
6186-6234'	Spot 100 gals 20% IC HCL
	Acidize with 1900 gals 20% IC HCL and 114 ball sealers
5974-6018'	Spot 50 gals 15% IC HCL
	Acidize with 1750 gals 15% IC HCL
5452-5578'	Spot 125 gals 15% IC HCL
	Acidize with 4000 gals 15% IC HCL + 126 ball sealers