

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED

5a. Indicate Type of Lease  
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS MAY 12 1980

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> O. C. D. ARTESIA, OFFICE	7. Unit Agreement Name
2. Name of Operator McClellan Oil Corporation	8. Farm or Lease Name Jack L.
3. Address of Operator P. O. Drawer 730, Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER M, 860 FEET FROM THE South LINE A. 660 FEET FROM THE West LINE, SECTION 14 TOWNSHIP 6-S RANGE 27-E NMPM.	10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4106 G. L. 4119 D. F.	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING O-NIS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/30/80: Drilled to 40'. Ran 40' of 13-3/8" new J-55, 54-1/2 lb. casing cemented with 6 yards ready-mix, to surface.

5/03/80: Drilled to 1486'. Ran 1447' of new 20 lb., J-55, 8-5/8" casing. Cemented with 450 sx Pacesetter Lite, 3% gel & 200 sx Class "C", 2% CaCl. Circulated 100sx cement.

5/04/80: Waited 18 hours drilled out plug. Tested 250 lbs. 30 minutes. Pressure held. Drilling ahead.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Joe J. Mc Clellan</u>	TITLE <u>Operator</u>	DATE <u>5/09/80</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>MAY 13 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		