

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State <input type="checkbox"/> Free <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT..." (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	AUG 4 1980	7. Unit Agreement Name
2. Name of Operator McClellan Oil Corporation	O. C. D. ARTESIA OFFICE	8. Farm or Lease Name Jack L.
3. Address of Operator Drawer 730, Roswell, New Mexico 88201		9. Well No. 1
4. Location of Well UNIT LETTER M 860 FEET FROM THE South LINE A-B 660 FEET FROM THE West LINE, SECTION 14 TOWNSHIP 6-S RANGE 27-E N.M.P.M.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4106' GL 4119' DF		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING O.N.S. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This test was perforated as follows; 5019-5036. Set wireline bridge plug at 5005'. 4943-4984; 4836-4868; 4737-4782. One shot/ft. over these intervals at various depths.

Propose to P&A this test by spotting cement plugs with heavy mud between plugs as follows: 4700'-5005'; 100' plug over stub of 4 1/2" casing at approximately 4200'. (Top of cement by temp. survey-4270'). 100' plug in and out of 8 5/8" csg. 1400'-1500'. 10 sx. plug at surface. Set dry hole marker. Pits and location will be utilized for drilling the 1-X.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Joe J. McClellan TITLE Operator DATE 8/02/80

APPROVED BY W.A. Gussett TITLE SUPERVISOR, DISTRICT II DATE AUG 6 1980

CONDITIONS OF APPROVAL, IF ANY:

Spota 35 SK Plug 2470-2570