

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

JUN 25 1980

**O. C. D.**  
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-5029

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Hanagan Petroleum Corporation ✓	8. Farm or Lease Name Newmill-State
3. Address of Operator P.O.Box 1737 Roswell, New Mexico 88201	9. Well No. 1
4. Location of Well UNIT LETTER <u>0</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>27</u> TOWNSHIP <u>4 South</u> RANGE <u>27 East</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3953 GL	12. County Chaves

15. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 13 3/8" 48# ST & C Csg. set @ 147' cemented with 65 sx. Class "C" 2% Ca Cl, cmt. circ., plug down @ 9 PM (5/8/80), WOC 36 hrs.

Ran 8 5/8" 23# ST & C Csg. set @ 1332" (16' below top of San Andres) cemented with 125 sx. Howco lite plus 100 sx. Class "C" cement w/no additives, cmt. did not circ., plug down @ 6 PM (6/20/80), WOC 64 hrs. Now drilling 8" hole below 8 5/8" csg. with cable tools. Spud date, as already reported, was 4/30/80. Filled backside 8 5/8" csg. w/8 yds. ready mix cement.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Hugh C. Hanagan TITLE Vice-President DATE 6/24/80

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE JUN 26 1980

CONDITIONS OF APPROVAL, IF ANY: