1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Ì	1	U	16.	LUIV	15E1	4 V A	1101	וע צ	v 15	ION	ı				
DISTRIBUTION	1		-			P. C	). BO	K 2088			_					
SANTA PE	1			SAN	ATK	FE,	NEW	MEX	ICO E	3750	1					
FILE	1	7						•						50.	. Indi	cal
U.1.0.1.														ļ	Stat	٠ [
LAND OFFICE	-													5.	State	0
OPERATOR	11_			•												,
(UO NOT USE THIS FOR USE '			NOTICES							INT R	REC	oia.	WED		Unit	1/2
OIL XX WELL			OTHER-													
ome of Operator						-				A	UG '	7	1980	8.	Foar	

Forn C-103

SANTA FE, NEW MEXICO 87501	
rice 1 V	50. Indicate Type of Lease
U.S.O.S.	State Ton X
LAND OFFICE	5. State Oli & Gas Lease No.
OPERATOR	1
	THE THE THE THE
SUNDRY NOTICES AND REPORTS ON WELLS	
	VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
RECIDIVED	7. Unit Agreement Nome
OIL XX WELL OTHER-	
2. Name of Operator AUG 7 1980	B. Farm of Lease Hame
Stevens Oil Company	O'Brien "I"
3. Address of Operator O. C. D.	9. Well No.
	6
P.O. Box 2203, Roswell, N.M. 88201 ARIESIA, CIEFICE	10. Field and Pool, or Wildean ASS
4. Location of Well	Twin Lakes-San Andr
UNIT LETTER K . 1650 FEET FROM THE SOUTH LINE ALT 1650 FEET FROM	TWIN LAKES BAH INIGI
THE West LINE, SECTION 31 TOWNSHIP 8-S RANGE 29-E NMPM.	
THE WEST LINE, SECTION 32 TOWNSHIP 3	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Charres ()
3986.4 Gr, 3991.4 KB	Chaves (1)
Check Appropriate Box To Indicate Nature of Notice, Report or Oth	ner Data
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF:
Notice of my envious	
BLUC AND ANANDON REMEDIAL WORK	ALTERING CASING
PERFORM REMEDIAL WORK	PLUG AND ABANDCAMENT
TEMPORABILY ABANDON COMMENCE DRILLING 01:45.	PEGG AND ABANDONALITY
PULL OR ALTER CABING CASING TEST AND CEMENT JOB XX	۲
OTHER	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any propos
work) SEE RULE 1103.	
4-05-80 Staked Location.	
4-06-80	
thru	
4-19-80 Building location and roads.	

- 7-01-80 Moving in rig.
- 7-06-80 Prep to spud.
- 7-08-80 Spud at 7:00 AM. Ø 132'. Ran 121' 8-5/8" 24# surface casing. Cemented with 75 sacks Class "C" 2% calcium chloride cement. WOC 18 hours. Pressured up to 1000# for 30 minutes, logging no pressure decline, drilled out and drilled ahead.
- 7-21-80 Ran 2900' 4-1/2" 9.5# casing. Cemented with 125 sacks self-stress cement. WOC
- 7-31-80 Perf. 2697,97.5,98,2718.5,19,19.5,23,23.5,24,24.5,34.5,38.5,39. Acidized with 5000 gal. 28% acid.

		·
18. I hereby deriffy that the information above is true and com	plete to the best of my knowledge and belief.	8-6-80
CONDITIONS OF APPROVAL, IF ANY:	SUPERVISOR, DISTRICT II	AUG 1 1 1980