

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp</u>		Lease <u>Selman Draw NR State</u>		Well # <u>1</u>	
Location of Well	Unit <u>J</u>	Section <u>9</u>	Township <u>7</u>	Range <u>24</u>	County <u>Chaves</u>
Drilling Contractor	<u>La Rue</u>		Type of Equipment <u>Rotary</u>		
* witness					

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>	<u>48#</u>		<u>450</u>	<u>Circ</u>
* <u>12 1/4</u>	<u>8 5/8</u>	<u>24#</u>		<u>1500</u>	<u>Circ</u>
<u>7 7/8</u>	<u>4 1/2 or 5 1/2</u>	<u>10.5 or 11.6</u> <u>14 5/8</u>		<u>4060</u>	<u>250 SX</u>

Casing Data:

Int
Surface 34 joints of 8 5/8 inch 24 # Grade J-55
(Approved) (Rejected)

Inspected by mw date

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 865 SX

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded Yes

TD of hole 1545 Set 1557 Feet of 8 5/8 inch 24 # Grade J-55

New-used csg. @ 1545 with 150 sacks neat cement around shoe
+ 715 sax 65/35 Poz additives 2# Kdite/sk - 1/4# Floetec/sk 32CL

Plug down @ 7:45 (AM) (PM) Date 4/26/80

Cement circulated Yes No. of Sacks 40 SK

Cemented by Dewell Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Basket c 1000' Lost some line c 1115'