

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYN.M.O.C.D. COPY  
SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved. C.S.P.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such purposes.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM - 14982
2. NAME OF OPERATOR MESA PETROLEUM CO. ✓		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 1980' FWL		8. FARM OR LEASE NAME STANCEL FEDERAL
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3996.5' GR		10. FIELD AND POOL, OR WILDCAT WILDCAT
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC 23, T5S, R24E
		12. COUNTY OR PARISH CHAVES
		13. STATE NEW MEXICO

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spudding &amp; 13-3/8" casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Spudded well with 17-1/2" hole on 5-18-80 and drilled to 296'. Ran 7 jts 13-3/8", 48#, H-40, ST&C casing for a total length of 296.58'; set at 296'; FC at 255'; and centralizers at 291', 255', and 165'. Cemented with 320 sx Class "C" + 2% CaCl. PD at 5:00 PM 5-18-80. Circulated 75 sx to pit. WOC total of 8 hours. Reduced hole to 11", drilled out cement and then drilled ahead without BOPs on 5-19-80.

RECEIVED

MAY 23 1980

O. C. D.  
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct:

SIGNED

R. E. Mathews

TITLE Regulatory Coordinator

DATE 5-20-80

(This space for Federal or State office use)

APPROVED BY

JOHN GEORGE H. TEWARI

TITLE

DATE

MAY 23 1980

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

XC: USGS (6), TLS, JWH, CENT RCDS, ACCTG, PLE, MEC, JBH, FILE