

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED  
JUN 2 1980

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> For <input type="checkbox"/>
5. State Oil & Gas Lease No. L-4666

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Argee Oil Company ✓	8. Farm or Lease Name Latham State
3. Address of Operator 810 C & K Petroleum Bldg., Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>P</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>25</u> TOWNSHIP <u>10S</u> RANGE <u>26E</u> NMPM.	10. Field and Pool, or Wildcat Und. Brown Queen-G.
15. Elevation (Show whether DF, RT, GR, etc.) 3705 GR.	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well 8:00 AM, May 21, 1980. Drilled 10" hole to 280'. Set 257', 8 5/8" 20# STC casing at 263' below rig floor. Cemented with 100 sax (106 cu.ft.) Class "C", 2% CaCl<sub>2</sub>. Cement circulated to surface. WOC 18 hours. Bailed hole dry to check for leakage. No leakage in one hour.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. Schuenter TITLE Agent DATE 5/26/80

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 3 1980

CONDITIONS OF APPROVAL, IF ANY: