

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088

RECEIVED BY NEW MEXICO 87501

Form C-103  
Revised 10-1-78

FEB 28 1985

O.C.D.

3a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
V-1361

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PROPOSAL TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR" FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Quanico Oil & Gas, Inc.	8. Farm or Lease Name Latham-State
3. Address of Operator 1710 North Union # 7, Roswell, NM 88201	9. Well No. # 1
4. Location of Well UNIT LETTER P 330 FEET FROM THE South LINE AND 330 FEET FROM THE East LINE, SECTION 25 TOWNSHIP 10 South RANGE 26 East NMPM.	10. Field and Pool, or Wildcat Brown-Queens
15. Elevation (Show whether DF, RT, GR, etc.) 3705 GR	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒  
COMMENCE DRILLING OPS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1-26-85-Perforated Queens sand from 628' to 650' w/2 SPF and 700' to 710' w/2 SPF. Acidized each interval w/500 gallons 15% Spearhead acid. Cement broke down and had communication. Swabbed down with slight show of oil. Squeezed perfs 628' to 650' and 700' to 710' w/400 sacks. Shut in-W.O.C.

2-6-85-Drilled out Cement to 657'.

2-7-85- Reperforated Queens sand from 632' to 648' w/2 SPF and 616' to 620' w/4 SPF. Attempted to Acidize with 1000 gallons 15% Spearhead acid. Cement broke down again and had communication. Swabbed back load and swabbed dry with no-show. Shut down awaiting further orders.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Douglas K. Allen TITLE VICE-PRESIDENT

DATE 2-21-85

APPROVED BY Leslie A. Clements TITLE Superintendent District II

DATE MAR 11 1985

CONDITIONS OF APPROVAL, IF ANY: