

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petroleum Corp</u>		Lease <u>West Dixon N. State</u>		Well # <u>1</u>	
Location of Well	Unit <u>1980 6601 E</u>	Section <u>27</u>	Township <u>7</u>	Range <u>24</u>	County <u>Chaves</u>
Drilling Contractor	<u>La Rue</u>		Type of Equipment <u>Rotary</u>		

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48#		292' 456'	Circ
12 1/4	8 5/8	24#		1500	Circ
7 7/8	4 1/2 or 5 1/2	10.5# - 11.6# 14 - 15.5#		5500	—

Casing Data:

17 1/2" hole to 412'

Surface joints of 8 5/8" inch 24 # Grade J-55

(Approved) (Rejected)

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____

Type of Shoe used guide Float collar used insert Btm 3 jts welded yes

TD of hole 1560' Set 1560' Feet of 8 5/8" Inch 24 # Grade J-55

New-used csg. @ 1560' with 150 2% cc sacks neat cement around shoe
+ 550 sack Hall's additives 5# gilsonite, 1/4# flocc, 2% cc

Plug down @ 11:45 (AM) (PM) Date 5/28/80

Cement circulated No No. of Sacks -0-

Cemented by Hall-Dunton Witnessed by Mike Stillefield

Temp. Survey ran @ 6:00 (AM) (PM) Date 5/29/80 top cement @ 320'

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks:

No centrifuges