

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	1
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 12-1-78

Corrected Report

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Lease <input checked="" type="checkbox"/>
5. State (Oil) 6. Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
O'Brien "F"	
9. Well No.	
5	
10. Field and Pool, or Wildcat	
Assoc. Twin Lakes-San Andre	
12. County	
Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

1. Name of Operator
Stevens Oil Company

2. Address of Operator
P.O. Box 2203, Roswell, N.M. 88201

3. Location of Well
UNIT LETTER P 330 FEET FROM THE South LINE AT 990 FEET FROM
THE East LINE, SECTION 35 TOWNSHIP 8-S RANGE 28-E N.M.P.M.

RECEIVED

AUG 8 1980

O. C. D.

ARTESIA, OFFICE

15. Elevation (Show whether DF, RT, GR, etc.)
3930.4 Gr, 2936.4 KB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPER. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 5-19-80 Staked Location.
- 5-31-80 Spud 8:00 AM. Drilled 138' and ran 126' 8-5/8" 20# surface casing. Circulated cement with 75 sacks Class "C" cement. WOC 18 hours. Pressured to 1000#/30 min. Logging no pressure decrease. Drilled out and drilled ahead.
- 5-12-80 Ran 2703' 4-1/2" 9.5# casing and cemented with 125 sacks MOR cement. WOC/18 hours. Pressured to 1000#/30 minutes. Logging no pressure decrease.
- 5-24-80 Perf. 2568.5, 69, 69.5, 73.5, 74, 74.5, 80.5, 81, 81.5, 84.5, 85, 85.5, 87, 87.5, 88.
- 5-26-80 Acidized with 5000 gal. 28% acid. Testing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Donald G. Hume* TITLE Owner DATE 8-7-80

APPROVED BY *W.A. Gessett* TITLE SUPERVISOR, DISTRICT II DATE AUG 11 1980

CONDITIONS OF APPROVAL, IF ANY: