

4/5F

File

JAN 12 1991

O. C. D.

ARTESIA OFFICE

SUNDRIY PRODUCTION

USE APPROPRIATE FOR PRODUCTION

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry Hole

2. NAME OF OPERATOR NRM PETROLEUM CORPORATION ✓

3. ADDRESS OF OPERATOR 900 Bldg. of the Southwest Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
A. Surface 1980' FNL & 1983' FEL, Sec. 8, T-5-S, R-29-E
Chaves County, New Mexico

14. PERMIT NO. 3667.3 GR

15. ELEVATIONS (Show whether DT, RT, CR, etc.)

16. FEDERAL '8' 9. WELL NO. 1

10. FIELD AND POOL, OR WILDCAT Ellenburger

11. SEC., T., R., M., OR P.M. AND SURVEY OR AREA Sec. 8, T-5-S, R-29-E

12. COUNTY OR PARISH Chaves

13. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	☐	FULL OR ALTER CASING	☐	WATER SHUT-OFF	☐	REPAIRING WELL	☐
FRACURE TREAT	☐	MULTIPLE COMPLETION	☐	FRACURE TREATMENT	☐	ALTERING CASING	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐	SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☒
REPAIR WELL	☐	CHANGE PLANS	☐	(Other)	☐		

17. IS ROPE PROPOSED OR COMPLETION OPERATIONS? (Indicate state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and cones pertinent to this work.)

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

The Federal "8" #1 spudded 7-22-80 @ 6 p.m. Set 8 jts. 12-3/4" casing @ 322' & cmt. w/350 sx Cl C w/2% CC. Drld. to 3400'. Set 83 jts. 8-5/8" csg. @ 3400' & cmt. w/820 sx Cl H 50/50 Poz w/6# salt/sk + .5% CFR-2. Drld. to 6270'. Ran DST #1 6142'-6270'. Pkr. failed. Ran DST #2 6094'-6270'. Pkr. failed. Drld. to 7916'. Ran DST #3 7845'-7916'. Rec. 3' DM. FSIP 430#. Drld. to 7975'. Ran DST #4 7924'-75'. Rec. 5475' formation wtr. FSIP 2921#. Drld. to TD 8192'. On 8-29-80 Schlumberger ran open hole logs. On 8-30-80 plugged back to 2875'. On 9-10-80 McCullough ran GR collar log. On 9-10-80 perforated 2658'-2664' (7 holes) & set 79 jts. 2-3/8" tbg. @ 2600'. Western acidized w/1000 gals. 15% HCL acid. Avg. press. 1800#, AIR .9 BPM. On 9-12-80 ran GR neutron & base temp. log. Western acid. perfs w/3000 gals. 15% CRA. Avg. press. 2250#, AIR 3.8 BPM. Swbd. Rec. 87 BLW w/63 BLTR. On 9-15-80 swbd. to SN w/no fluid entry. On 9-16-80 pulled tbg. & pkr. & spot 35 sx cmt. plug 2714'-2688', 15 sx plug @ surface. Well P&A.

Post ID-2
P+A
1-15-31

18. I hereby certify that the foregoing is true and correct

SIGNED Joanne Finley Joanne Finley TITLE Production Secretary

(This space for Federal or State office use)

DATE 12-1-80

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side