

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	1	✓
FILE	1	
U.S.O.I.		
LAND OFFICE		
OPERATION	1	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG-155

SUNDARY NOTICES AND REPORTS ON WELLS RECEIVED
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER- 2. Name of Operator Yates Petroleum Corporation ✓ 3. Address of Operator 207 South 4th Street - Artesia, NM 88210 4. Location of Well UNIT LETTER L 660 FEET FROM THE West LINE AND 1980 FEET FROM THE South LINE, SECTION 31 TOWNSHIP 4S RANGE 25E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3902' GR	6. Unit Agreement Name O. C. D. 7. Unit Agreement Name ARTESIA, OFFICE 8. Farm or Lease Name Willow Creek Unit 9. Well No. 2 10. Field and Pool, or Wildcat Wildcat P. 11.1 12. County Chaves
---	--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moved in Link Rat Hole Digger and spudded a 24" hole at 10:00 PM 6-30-80. Drilled to 29' GR and set 29' of 20" conductor pipe and cemented w/1-1/2 yards of Ready-mix. Moved out Rat Hole Digger and moved in Rotary Tools. Started reaming a 17½" hole w/Rotary at 6:00 PM 7-11-80. TD 495' - Ran 13 joints of 13-3/8" 48# K-55 ST&C (495') of casing set at 495'. 1-Flapper float at 456'. Cemented w/450 sacks Class C 4% CaCl. Slurry weight 14.8, 1.32 cu ft/sack. Compressive strength at 70 degrees 1023 psi in 12 hours. PD 10:15 AM 7-12-80. Circulated 20 sacks of cement to the surface. WOC 12 hours, backed off, reduced hole to 7-7/8", drilled plug, tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine J. Johnson</u>	TITLE <u>Geol. Secty.</u>	DATE <u>7-30-80</u>
APPROVED BY <u>Mike Williams</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>JUL 31 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		