

AFTER

Spot 50' Surface Stevens Operating Co.
plug. MPANY

LEASE & WELL NO. RMA Fed. #1

FORMATION
COUNTY & STATE Chaves, New Mex.

RAYMOND MALDONADO
SUPERVISOR, P & A OPERATIONS
BUS. (505)393-9171
FAX (505)393-3848
MOBILE (505)390-0540

8 5/8 1400' CMT. W/500 SX Cement Circulated

Spot 100' cement plug across 8 5/8 shoe at 1450' & tag

Spot 120' cement plug at 2610' - 2490'

Spot 140' stub plug & tag

TOC 4700 CAL. Cut 4 1/2 casing at free point out of hole

Set CIBP at 5000' Cap w/55' cement

Perfs 5015 - 5098

FBTD = 6305' CIBP - CAP at 6305' w/35' cement

Perfs. 6605' - 6615'

4 1/2 6810' TD

CONVERSION FACTORS

MULTIPLY	By	TO OBTAIN
Barrels	5.6146	Cubic Feet
Cubic Feet	7.4806	Gallons
Gallons	0.1337	Cubic Feet
Pounds/gal.	7.4806	Pounds/Cu. Ft.

PIPE VOLUMES

0.00545 x I.D. in inches = Cu. Ft./Ft.
0.0407 x I.D. in inches = Gals./Ft.
0.00097 x I.D. in inches = Bbls./Ft.

HYDROSTATIC PRESSURE

FOR WATER:
0.434 x Depth in Feet = PSI.
FOR OTHER FLUIDS:
0.434 x Depth x Sp. Gr. = PSI.