

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI-STATE
(Other instruction on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-A-12125

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER ☐ AUG 13 1980

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street-Artesia, NM 88210

ARTESIA OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FWL & 1980' FNL of Section 25-7S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3641' GR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Coffman NY Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25-7S-25E

Unit E NMPM

12. COUNTY OR PARISH 13. STATE

Chaves

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

Spudded a 17½" hole at 12:00 noon 8-1-80.

TD 430' - Ran 11 joints of 13-3/8" 48# K-55 ST&C (432') of casing set at 430'. 1-Flapper float at 384'. Cemented w/420 sacks of Class C 4% CaCl. PD 10:30 PM 8-1-80. Circulated 5 sacks of cement to the surface. WOC 12 hours, backed off, reduced hole to 12¼", drilled plug and tested to 600# OK and resumed drilling.

TD 1600' - Reduced hole to 7-7/8" to test loss circulation zone. Ran 32 joints of 8-5/8" 24# K-55 (1384') of casing set at 1383'. 1-Texas Pattern guide shoe at 1383' and insert float at 1339'. Cemented w/800 sacks 65/35 Poz, 4% Bentonite, 8# Kolite, 1/4# celloflakes, 3% CaCl. Tailed in w/150 sacks of Class C 2% CaCl. PD 10:30 AM 8-5-80. Circulated 50 sacks of cement to the surface. WOC 18 hours, NU and tested to 1500# OK, reduced hole to 7-7/8", drilled plug and tested to 600# OK, resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tombeuse

TITLE

Geol. Secty.

DATE

8-7-80

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

AUG 13 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO