

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

RECEIVED

JUL 23 1992

WELL API NO.

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Moonlight 33 West

8. Well No.

1

9. Pool name or Wildcat

Wildcat San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Bridge Oil Company, L. P.

3. Address of Operator

12404 Park Central Dr., Ste. 400, Dallas, TX 75251

4. Well Location

Unit Letter J : 1980 Feet From The South Line and 1980 Feet From The East Line

Section 33

Township 7S

Range 28E

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3978.4 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU Pride Well Service on 7/17/92. Plugged and abandoned well as follows:
TOH with 2 3/8" tbg. Set 4 1/2" CIBP at 2303'. Spotted 5 sx Class "H" cement
plug from 2308' to 2273'. Circ well with 10# gel brine. Spotted 10 sx Class
"H" cement plug from 1925' to 1825'. RU wireline and shot casing at 1300'.
TIH with cement retainer and 2 3/8" tbg. Set retainer at 1250'. Pumped
280 sx Class "H" cement and circulated cement to surface. Pulled out of
retainer and spotted 10 sx Class "H" cement plug from 1250' to 1150'. Spotted
10 sx Class "H" cement plug from 750' to 650'. Spotted 16 sx Class "H" cement
plug from 190' to surface. Cut and capped well. Installed dry hole marker and
cleaned location. Well P&A'd. Gary Williams (NMOCD) notified but did not witness.

Post ID-2
8-7-92
PFA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rhonda Sutton

TITLE

Regulatory Coordinator

DATE

7/17/92

TYPE OR PRINT NAME

Rhonda Sutton

214/788-3371

TELEPHONE NO.

(This space for State Use)

APPROVED BY

Johnny Robinson

TITLE

INSPECTOR

DATE

9-11-92

CONDITIONS OF APPROVAL, IF ANY:

OK
GW