

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

*Plugging*  
FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Wayne J. Spear</i>		Lease <i>Zimmerman</i>		Well # <i>1</i>	
Location of Well	Unit <i>C-2 HERU</i>	Section <i>35</i>	Township <i>10 S</i>	Range <i>25 E</i>	County <i>Chaves</i>
Plugging Contractor	<i>Cap Fulton</i>		Type of Equipment <i>Pulling unit</i>		
<i>in Hole</i> <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>9 5/8 x 7 7/8</i> <i>6 1/4</i>	<i>4 1/2</i>	<i>9 1/2</i>	<i>New</i>	<i>1226 1/2</i>	<i>625 lined to</i> <i>perfs.</i> <i>1218-1226 1/2</i>
Casing Data:					
Surface _____ joints of _____ inch # Grade _____ (Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole _____ Size of Casing _____ Sacks cement required _____					
Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____					
TD of hole _____ Set _____ Feet of _____ Inch # Grade _____					
New-used csg. @ _____ with _____ sacks neat cement around shoe					
+ _____ sack _____ additives _____					
Plug down @ _____ (AM) (PM) Date _____					
Cement circulated _____ No. of Sacks _____					
Cemented by _____ Witnessed by _____					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

- Well was plugged as follows.*  
*Hole loaded with mud between plugs. 3-25-63 H.L.*
- 1. 24 sks at T.O. - 3-25-63 H.L.*
  - 2. 10 sks at 400' 3-25-63 H.L.*
  - 3. 5 sks. in surface*

