

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRII ATE*
(Other instruction on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR MESA PETROLEUM CO		8. FARM OR LEASE NAME STANCEL FEDERAL	
3. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701		9. WELL NO. 3	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1980' FWL		10. FIELD AND POOL, OR WILDCAT UNDESIGNATED ABO	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC 22, T5S, R24E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4031.4' GR		12. COUNTY OR PARISH CHAVES	
		13. STATE NEW MEXICO	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) 8 5/8" CSG & CEMENT <input checked="" type="checkbox"/>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 1345' on air, hit small salt water flow, switched to foam and drilled to 1859' on 12-30-80. Ran 8 5/8", 24#, J-55 casing set at 1858' with insert float at 1824' and centralizers on jts 1, 3, & 5. Cemented with 200 sx Thixset + 15# gilsonite + 3/4# flocele + 2% CaCl followed by 200 sx Lt + 15# gilsonite + 3/4# flocele + 2% CaCl and tailed in with 200 sx "C" + 2% CaCl. PD at 8:45 AM 12-31-80. Circulated 122 sx to pit. WOC 11 3/4 hours, tested casing & BOP's to 600 psi for 30 min - OK. Reduced hole to 7 7/8" and drilled ahead on 1-1-81.

XC: USGS (6), TLS, HOBBS OFFICE, MEC, PARTNERS, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED R. F. Nathan TITLE REGULATORY COORDINATOR DATE JANUARY 5, 1981

(This space for Federal AGENT FOR RECORD)

APPROVED BY PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY JAN 8 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO See Instructions on Reverse Side