

44-41. O.C.D. COPY

UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 23264

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SALT FEDERAL

9. WELL NO.

1

O. C. D.
ARTESIA OFFICE

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLE. AND
SURVEY OR AREA

SEC 8, T8S, R23E

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

MESA PETROLEUM CO

3. ADDRESS OF OPERATOR

1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 660' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4106.7' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spudding & Cementing ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.) *

Spudded well with 12 1/4" hole on 11-18-80. Drilled to 930' with air and ran 23 jts of 8 5/8", 24#, K-55 casing, set at 930'. Cemented with 200 sx Thixoment, 500 sx Lite and tailed in with 200 sx "C" + 2% CaCl. Cement did not circulate. Ran temperature survey, TOC at 590'. Set 4 plugs with total of 400 sx, circulated 10 sx to pit. Reduced hole to 7 7/8" on 11-22-80, tested BOP & csg to 600 psi for 30 mins - OK. Drilled to 1045' with air, hit salty water and drilled with mist to 1841', hit additional wtr. Mudded up with 180 bbls @ 2458'.

RECEIVED

NOV 28 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

XC: USGS (6), TLS, CEN RCDS, ACCTG, MEC, MAH, HOBBS OFFICE, PARTNERS, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Regulatory Coordinator

DATE

11-24-80

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

DEC 4 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side