		• ~		
STATE OF NEW MEXICO				
NERGY AND MINERALS DEPARTMENT				
	OIL CONSERVATION DI	IVISION	÷.	
DISTRIBUTION	P. O. BOX 2088	RECEIVED	() ()	Form C-103
SANTA PE	SANTA FE, NEW MEXICO	87501		Revised 10-1-78
The	· · · · · ·		·	
V.3.0.3.		NOV 1 3 1980	So, Indicate Type o	
LAND OFFICE			· State X	500
OPERATOR		C. C. D.	5, State Oti & Gas	Lease No.
		ARTEUR CREWE	L-6779	i
SUNDAY N	OTICES AND REPORTS ON WELLS		MILLION A	mmm
LON NOT USE THIS FORM FOR PROPOSA USE "APPLICATION F				
USE "APPLICATION P	7. Unit Agreement	7/11/11/11		
	•		7, Ont Agreement	Nome
	OTHER-			
Name of Operator			8. Farm or Lease liame	
Yates Petroleum Corporation			Long Arroyo	OD State Co
Address of Operator			9. Well No.	
207 South 4th St., Arte	sia, NM 88210			
Location of Well		<u></u>	10. Field and Pool	of Wilder
UNIT LETTER I 2310 FEET FROM THE South LINE AND 660 FEET FROM				
UNIT LETTER , 2310	Und. Morrow			
THE East LINE, SECTION	14 TOWNSHIP14S RANGE .	27E NMPM	$(\Lambda))))))))))))))))))))))))))))))))))))$	
			YIIIIII	
ANNIN ANN ANN ANN ANN ANN ANN ANN ANN AN	15. Elevation (Show whether DF, RT, GR,	e:c.)	12. County	XUUUUUU
	3473' GR		Chaves	
mmmm		• • • • • • • • • • • • • • • • • • •		mmm
	ropriate Box To Indicate Nature of N	otice, Report or Ot	her Data	•
NOTICE OF INTE	NTION TO:	SUBSEQUEN	T REPORT OF:	
·				
ERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL W		ALTERN	G CASING
CHPORARILY ASANOON	. COMMENCE D	RILLING OPHS.		D ABANDONMENT
ULL OR ALTER CASING		AND CEMENT JOB	· PLUG AN	
			aina	- (7)
		Production Ca	sing	[X]
07HER	L-J			
Describe Description of Completed Operation	ions (Clearly state all pertinent details, and give			·····
, Describe Proposed or Completed Operation	ions locently state all pertinent actails, and give	pertinent dates, including	estimated date of st	arting any proposed

work) SEE RULE 1703, TD 8220' Ran 194 joints of 4-1/2'' 11.6# N-80 LT&C and 10.5# K-55 ST&C of casing as follows:

TD 8220' Ran 194 joints of 4-1/2" 11.6# N-80 LT&C and 10.5# K-55 ST&C of casing as follows: 39 joints of 4-1/2" 11.6#N-80 LT&C; 150 joints of 4-1/2" 10.5# K-55 ST&C; 5 joints of 4-1/2" 11.6# K-55 casing set at 8162'. 1-guide shoe at 8162'. Diff-fill float collar at 8114'. Cemented w/600 sacks 50-50 Poz, 2% gel, 4/10% Halad 22, 4/10% CFR2, 5#/sack KCL. Tailed in w/200 sacks Class "H", 4/10% Halad 22, 4/10% CFR2 and 5#/sack KCL. PD 10:30 AM 11-7-80. Ran Temperature Survey and found top of cement at 5000'. PBTD 8078'. WOC and tested to 1500 psi, OK.

nereby certify that the information above is true and co	mplete to the best of my knowledge and belief.	
_ (Albert K Math	Engineer	DATE NOV. 11, 1980
wir W.a. Aresset	SUPERVISOR, DISTINCE II	NOV 171980