

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

AUG 11 1993

WELL API NO.
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. L-6779
7. Lease Name or Unit Agreement Name Long Arroyo OD State Com
8. Well No. 1
9. Pool name or Wildcat Undesignated
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3473' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter I : 2310 Feet From The South Line and 660 Feet From The East Line Section 14 Township 14S Range 27E NMPM Chaves County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3473' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: Add Atoka & Strawn perms. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

CONTINUED FROM PREVIOUS PAGE:

- If decision is made to produce Atoka/Morrow and not add Strawn, will TOOH w/RBP and packer. TIH w/packer with on/off tool and swab well in.
- If decision to add Strawn is made, will straddle proposed interval with RBP and packer. Swab tubing down to 7000'. Perforate Strawn from 7587-7601' w/18 holes (2 SPF) as follows: 7587, 88, 89, 90, 97, 98, 99, 7600 & 7601'.
- Will test Strawn if it comes in flowing.
- Acidize perforations with 2000 gallons 7-1/2% Morflow acid containing 1000 scf/bbl nitrogen with ball sealers.
- Swab back spent acid. If decision is made to frac, will frac with binary or 30% CO2 gel, 15000-20000# 20-40 Ottawa or resin coated sand.

NOTE: Morrow/Atoka will be isolated from Strawn until commingling application has been approved by OCD.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE August 5, 1993  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY  
MIKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE  DATE 2/17/94

CONDITIONS OF APPROVAL, IF ANY: