

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 16094
2. NAME OF OPERATOR Southland Royalty Company /		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 1100 Wall Towers West: Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1780' FEL Sec. 29, T-14-S, R-27-E		8. FARM OR LEASE NAME Hagerman Federal "29" Comm
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3434.6 GR		10. FIELD AND POOL, OR WILDCAT Wildcat
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 29, T-14-S, R-27-E
		12. COUNTY OR PARISH Chaves
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set 11 3/4" Surface csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 15" hole 10-40-80. Drilled to 225'. Ran 6 jts of 11 3/4" 42#, H-40, ST&C csg & set @ 225'. Cmt w/250 sxs C1 "C" w/1% C.C. PD @ 6:45 PM, 10-14-80. Circ 75 sxs WOC 18 hr. Install 11 3/4" X 12" 3000# head. Install BOP. After 12 hr nipple up on BOP & pressure test BOP & 11 3/4" csg to 1000# for 30 min. Held OK. Compressive strength of C1 "C" w/1% C.C. is 2015 psi @ 95°F. Drill ahead w/11" bit.

RECEIVED

OCT 27 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

OCT 24 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

District Operations Engineer 10-22-80

DATE

(This space for Federal or State Office Use)

APPROVED BY
CONDITIONS OF APPROVAL IF ANY

TITLE

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side