Form 9-331 Dec. 1973 UNITED STATES DEPARTMENT OF THE INTERIOR	NS. COMMISSIL Furm Approved. Budget Bureau No. 42-R1424 NM 88210 5. LEASE NM-16094
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRI <b>REGASIL/ED</b>
SUNDRY NOTICES AND REPORTS ON WI (Do not use this form for proposals to drill or to deepen or plug back to reservoir. Use Form 9-331-C for such proposals.) 1. oil gas other DRY HOLE 2. NAME OF OPERATOR DWIGHT A. TIPTON 3. ADDRESS OF OPEF P.O. BOX 1597, LOVINGTON, NEW MEXICO & 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See s below.) AT SURFACE: 1980' FSL & 1780' FEL OF SE AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	a different  SAIN 13 1983    8. FARM OR LEASE NAME HAGERMAN 29 FEDERAL D.    9. WELL NO.    10. FIELD OR WILDCAT NAME WILDCAT    88260    space 17    EC. 29    12. COUNTY OR PARISH CHAVES
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF REPORT, OR OTHER DATA    REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT    TEST WATER SHUT-OFF	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3434 6 GR

CISE

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-23-82: Rigged up Pulling Unit and Reverse Rig. Drilled out retainer and cement plug to depth of 1025 feet. Perforated interval 1012-1020 feet. Acidized with 250 gallons and swabbed dry. 8-31-82: Propaging to Plug and Abander

8-31-82:	Preparing	to Plug	and	Abandon.
----------	-----------	---------	-----	----------

Subsurface Safety Valve: Manu. and Type	
SIGN D AFTHUR R. BYOWN AGE	nt December 27, 1982
APPROVED BY CONDITIONS OF APPROVAL IF 1N1 1983	al or State office use)
MINERALS MANAGEMENT SERVICE ROSWELL, NEW MEXICO +See Instructions	on Reverse Side