

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	✓
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

OCT 24 1980

ARTESIA, NM

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Kuykendall OP Corn.
3. Address of Operator 207 So. 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>11</u> TOWNSHIP <u>6S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat Und. Abo
15. Elevation (Show whether DF, RT, CR, etc.) 4350' GR	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Spudded a 17-1/2" hole at 5:30 PM 10-16-80.
TD 819' Ran 10 joints of 13-3/8" 54.5# K-55 ST&C casing set at 401'. Notched guide shoe at 401'. Flapper float at 360'. Cemented w/400 sacks Class "C" 4% CaCl. Slurry weight 14.8, 1.32 cu ft/sack. Compressive strength at 70 degrees 1023 psi in 12 hours. PD 2:00 PM 10-19-80. Cement did not circulate. Filled hole w/7 yards Ready Mix. WOC 12 hours. Backed off and reduced hole to 7-7/8". Drilled plug and tested to 600#, OK. Resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall TITLE Engineer DATE 10-23-80

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE OCT 29 1980