

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instructions
verse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-20337

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bedford Fed Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated ABO

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 31, T6S, R25E

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Mesa Petroleum Co. ✓

3. ADDRESS OF OPERATOR

1000 Vaughn Building/Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1650' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3960.9' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other) Amend Drilling Program

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed to amend approved Drilling Program as follows:

Drill 17 1/2" hole to 800' on air. Set 13 3/8" casing and cement to surface. Reduce hole to 11" and drill to 1500' to set 8 5/8" casing. Nipple up ram type BOP's and reduce hole to 7 7/8" to drill to total depth using air, foam, or mud as required. After log evaluation, 4 1/2" casing may be run and cemented with sufficient kinds and amounts to isolate and seal off any fresh water, oil, or gas zones encountered after the casing point.

Gas Sales are not dedicated.

RECEIVED
JAN 15 1981U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

xc: USGS (6), TLS, HOBBS OFC, MEC, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED

R. P. Nathan

TITLE Regulatory Coordinator

DATE

1-9-81

(This space for Federal or State office use)

(Orig. 884) GEORGE H. STEWART

ACTING DISTRICT ENGINEER

APPROVED BY

TITLE

DATE

JAN 15 1981

CONDITIONS OF APPROVAL: set 17" water is encountered below the 13-3/4" casing, stop.