

U.S. GEOLOGICAL SURVEY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYU.S.G.D. COPY
SUBMIT IN TRIPI
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 20337

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

BEDFORD FEDERAL COM

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

UNDESIGNATED ABO

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC 31, T6S, R25E

12. COUNTY OR PARISH

CHAVES

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

MESA PETROLEUM CO. ✓

3. ADDRESS OF OPERATOR

1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface 1650' FSL & 1980' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3960.9' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) 8 5/8" CSG & CEMENT

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 11" hole to 1750' on 2-3-81. Ran 39 jts 8 5/8", 24#, K-55 casing set at 1749' with insert float at 1704'. Cemented with 350 sx Lt + 4% CaCl followed by 700 sx Thixset + 4% CaCl and 350 sx Lt + 4% CaCl, and tailed in with 300 sx "C" + 2% CaCl. PD at 3:45 PM. Circulated 60 sx to pit. WOC 8 1/2 hours, tested casing and BOP's to 600 psi - OK. Reduced hole and drilled ahead on 2-4-81.

XC: USGS (6), TLS, HOBBS, MEC, PARTNERS, FILE

18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. M...

TITLE REGULATORY COORDINATOR

DATE FEBRUARY 5, 1981

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

DATE

FEB 10 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side