

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Stevens Oil Company ✓	3. Address of Operator P.O. Box 2203, Roswell, N.M. 88201	4. Location of Well UNIT LETTER <u>P</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>1</u> TOWNSHIP <u>9S</u> RANGE <u>28E</u> N.M.P.M.	7. Unit Agreement Name	8. Farm or Lease Name O'Brien "E"	9. Well No. 4	10. Field and Pool, or Wildcat Assoc. Twin Lakes-San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3962.1 GR, 3972.1 KB				12. County Chaves			

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 10-06-80 Staked Location.
- 10-07-80 Building Location and roads.
- 10-28-80 Spud. Ran 80' 8-5/8" 20# surface casing. Cemented with 5 yards of ready-mix cement. WOC/24 hours.
- 11-17-80 TD 2800'. Ran 2800' 4-1/2" 9.5# casing. Cemented with 100 sacks Class "C" cement 2% calcium chloride and 75 sacks self-stress cement. WOC
- 11-25-80 Perfs. 2622.5, 23, 29.5, 31, 31.5, 34.5, 35, 36.5, 37, 39, 39.5, 40.5, 41, 45.5, 46, 46.5.
- 11-30-80 Acidized with 7,000 gals 28% acid. Flowed back and swabbed.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Owner DATE 12-9-80

APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE APR 23 1981

CONDITIONS OF APPROVAL, IF ANY: