

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.B.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

NOV 20 1980

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Stevens Oil Company ✓	8. Farm or Lease Name O'Brien "J"
3. Address of Operator P.O. Box 2203, Roswell, N.M. 88201	9. Well No. 3
4. Location of Well UNIT LETTER <u>G</u> <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>8S</u> RANGE <u>29E</u> NMPM.	10. Field and Pool, or Wildcat Assoc. Twin Lakes-San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3989.4 GR, 3999.4 KB	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-09-80 Staked Location.
10-10-80 Built Location and roads.
10-17-80 Spud. Ran 80' 8-5/8" 20# surface casing. Circulated with 5 yards Ready-Mix. WOC/18 hrs. Pressured to 1000#/30 min. Logging no pressure decrease. Drilled out and drilled ahead.
10-30-80 TD 2861'. Ran 2861' 4-1/2" 9.5# casing. Cemented with 100 sacks Class "C" cement and 75 sacks self-stress cement. WOC. Pressured to 1000#/30 min. Logging no pressure decrease.
11-06-80 Perf. 2709.5, 10, 10.5, 15.5, 16, 16.5, 19, 19.5, 20, 27.5, 28, 28.5, 31, 31.5, 32, 32.5, 35, 35.5, 36.5.
11-11-80 Acidized with 7,000 gal. 28% acid. Testing.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald G. Thur TITLE Owner DATE 11-19-80

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT III DATE NOV 21 1980

CONDITIONS OF APPROVAL, IF ANY: