

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 875017 1201

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

C. C. D.
ARTISANAL OFFICE

10. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

7. Unit Agreement Name

Name of Operator

8. Farm or Lease Name

Stevens Oil Company ✓
Address of Operator

O'Brien "F"

9. Well No.

P. O. Box 2203, Roswell, New Mexico 88201

8

Location of Well

10. Field and Pool, or Wildcat

UNIT LETTER C, 660' FEET FROM THE North LINE AND 1980' FEET FROM

Geological Wildcat

THE West LINE, SECTION 25 TOWNSHIP 8-S RANGE 28-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

12. County

3954 GL, 3969.5 KB

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

INFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
CUT OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

OTHER Perforating ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-25-81 Drilled out cement to 6375' T.D. Laid down drill pipe. Ran 3464' 5½" -17# liner. Set liner @ 6364', T/liner hanger @ 2901' (EL). Dowell cemented w/830 sacks Class "C", 320 sacks self-stress, circulated into 8 5/8" casing, reverse out 70 sacks Class "C". WOC 6 days, went in hole w/tubing, collars and 7 7/8" bit, used reverse unit to drill out to top of liner, pressured up to 1000# for 10 minutes, pressure held o.k. Ran 4 3/4" bit, drilled out to 6286' PBTD, came out w/tubing and bit, ran bond log. Showed good bond 4300' to T.D.- fair bond 2901' to 4300'. Perforated 5964.5, 65, 67.5, 68, 68.5, 71.5, 72, 76, 76.5, 88.5, 89, 95, 95.5, 99.5, 6000, 6000.5, 19, 19.5, 26.5, 27, 27.5, 28, 35, 35.5, 44.5, 45, 45.5, 48.5, 49, 49.5, 50, 56, 56.5.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

Owner

DATE 4-3-81

APPROVED BY

TITLE

OIL AND GAS INSPECTOR

DATE

APR 09 1981

CONDITIONS OF APPROVAL, IF ANY: