

N.M.O.C.D. COPY UNIT TO STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSTAMP IN TRIPPLICATE  
(Other Instructions  
to be filled in)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-12561

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒

Dry Hole

2. NAME OF OPERATOR

Inexco Oil Company ✓

3. ADDRESS OF OPERATOR

1100 Milam Building, Suite 1900

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface660' FNL & 1980' FWL  
1720

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3634.3 GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McClellan Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

31-13S-29E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☒(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set 13-3/8" 40# K-55 ST&C casing at 335' and cemented with 400 sack circulated to surface. Set 8-5/8" 24# K-55 ST&C casing at 2010' and cemented 900 sxs cemented circulated to surface. Drilled to 9200' logged and tested. Set 5 cement plugs consisting of 150 sxs each 9200-8757', 8895-8552', 7000-6557', 5000-4557', 3500-3057' also 2834-2650'. Set CIBP at 2350; and dumped 35' of cement on top of BP, placed cement 0-80'.

ACCEPTED FOR RECORD

FEB 6 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICORECEIVED  
FEB 6 1981  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Y. C. M. [Signature]

TITLE Drilling Administrator

DATE 1/30/81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE