

UNITED STATES NM OIL CONS. COMM. CON.
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
Artesia, NM 88210

Form approved,
Budget Bureau No. 42 R1424.
B. PLANS, DESIGNATION AND SERIAL NO.
NM-28297
C. IF INDIVIDUAL, LAST, FIRST OR TRIDE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.
Use APPLICATION FOR PERMIT for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	2. NAME OF OPERATOR Yates Petroleum Corporation ✓	3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210	4. LOCATION OF WELL (Report location clearly and in accordance with any State law or regulation. See also Space 17 below.) At surface 660' FSL & 660' FSL on Sec. 26-T5S-R24E	5. PERMIT NO. 3924' GR	6. ELEVATION (Show whether feet or meters) 3924' GR	7. NAME OF WELL Everette Oil Federal	8. WELL NO. 2	9. FIELD AND ZONE OR WILDCAT Wheat Abo	10. COUNTY OR PARCEL Chaves	11. STATE NM
--	--	--	--	---------------------------	--	---	------------------	---	--------------------------------	-----------------


16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	SHUT-IN DEEP	RELINING WELL
FRACTURE TREAT	MULTIPLE COMPLETION	SHUT-IN DEEPENMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHUT-IN ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	OTHER	ACIDIZE
(Other)			

*Not a report results of multiple completion on Well (and not a report of completion to port and log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS TO BEYOND SURFACE, pertinent depths, and, if pertinent, dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location and depth, and the vertical depths for all markers and zones pertinent to this work.*

TD 4200'. Ran 101 joints of 4-1/2" 9.5# K-55 SBC casing, set at 4150'. Auto-fill shoe at 4150'. Cemented w/350 sacks 50/50 Poz. 1.6" CFS, 1.3" TP-4 & 250 gallons Excello-gel. PD 6:45 AM 9-8-81. Bumped plug to 1200', released pressure & float held okay. WOC. WIH w/Steel Strip gun & perforated 3811-3905' w/13 .50" holes as follows: 3811, 19, 20, 21, 22, 25, 26, 3900, 01, 02, 03, 04 & 05'. Frac'd perforations w/1000 gallons 7-1/2" Spearhead acid. 90000 gallons gelled KCL water, 2 loads CO2, 90000# sand (80000# 20/40 mesh, 10000# 100 mesh). Well stabilized at 50 psi on 3/8" choke = 214 m f/d.



OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED WILLIAM A. CHAPMAN
(This space for Federal or State office use)

TITLE Engineering Secretary

DATE 10-20-81

APPROVED BY OCT 21 1981
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE