

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

SEP 28 1981

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
L-5252

O. C. D.

ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER- *Re Entry*

1. Name of Operator

AMMEX PETROLEUM, INC.

2. Address of Operator

Post Office Box 10507, Midland, Texas 79702

3. Location of Well

UNIT LETTER K 1980 FEET FROM THE South LINE AND 1980 FEET FROM
THE West LINE, SECTION 1 TOWNSHIP 8S RANGE 27E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Amoco State

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)
3949' G.L.

12. County
Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Subject well has been plugged and abandoned. Details are listed below.

- 8/18/81 Loaded hole with 9.5#/gal mud. Set 35 sacks Class "H" cement with 4% CaCl₂ at 5010'. Pulled 50 jts tubing and shut in overnight.
- 8/19/81 Ran tbg to 5041'. Did not tag cement. Loaded hole with 18 bbls 9.5#/gal mud. Spotted 35 sacks Class "H" cement with 4% CaCl₂ at 5010'. Pulled 50 jts tubing and shut in overnight.
- 8/20/81 Tagged cement plug at 4700'. Shot and pulled 4 1/2" casing from 2700'.
- 8/21/81 Ran tubing to 2720'. Circulated hole with 160 bbls 9.5#/gal mud. Spotted 40 sacks Class "H" cement with 4% CaCl₂ at 2720'. WOC two hours, tagged top of cement at 2620'. Spotted 35 sacks Class "H" cement with 4% CaCl₂ at 2112'. WOC two hours, ran tubing to 2240' and did not tag plug. Spotted 35 sacks Class "H" cement with 4% CaCl₂ at 2110'. WOC two hours, tagged top of cement at 2000'. Spotted 35 sacks Class "H" cement with 4% CaCl₂ at 416'.
- 8/22/81 Tagged cement plug at 273'. Laid down tubing. Set 10' cement plug at surface and installed dry hole marker.

Posted ID-2
P+ A
10-9-81

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bill Baker Bill Baker

TITLE Agent

DATE September 24, 1981

APPROVED BY Danell Moore

TITLE Geologist

DATE 1/4/89

CONDITIONS OF APPROVAL, IF ANY: