								-	1 0110	
NO. OF COPIES RECEIV	LO			.]:				30-00	5-60845	
DISTRIBUTION		NEW MEXICO OIL CONSERVATION COMMISSION					L _A T	Form C-101		
SANTA FE	1				RECEIVE		-	levised 1-1-6		
FILE								r -		
U.S.G.S.	.S.G.S.				JAN 071981			STATE		
LAND OFFICE						51		5. State Off	& Gus Loase No.	
OPERATOR	1		O. C. D.				Ļ			
						.				
APPL	ICATION	FOR PE	RMIT TO	DRILL, DEEPEN	I, OR PLUG'B	ACK		TIIII		
la. Type of Work	<u> </u>							7. Unit Agre	ement Name	
				DEEPEN		PLUGE				
DRILL X							8. Farm or Leuse Name			
1	GAS	о∵н			SINGLE X	MUL	ZONE	Moonshir	ne 10	
2. Name of Operator				······································				9. Well No.		
SelCo,	Inc. V							#1		
3. Address of Operator				· · · · · · · · · · · · · · · · · · ·				10, Field an	d Pool, or Wildon	
P.O. Box 798, Artesia, New Mexico 88210									Wildcat - Thus Labor	
4 Logation of Vall					FEET FROM THE	North	LINE	IIIII	<u>IIIIIIIIIIII</u>	
	UNIT LETTER		LOC	ATED	_ FEET FROM THE			///////		
1980 F	EET FROM T	JE East		E OF SEC. 10	TWP. 95	RGE. 28	BE NMPM			
YAD TAOD *			<u>iinni</u>		MIMM	ШП	IIIII	12. County		
	//////	//////	///////			IIIII	///////	Chaves		
<i>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</i>	<i>++++++</i>	++++++	HHHH	*******	<i>:////////////////////////////////////</i>	11111	<u>IIIIII</u>	IIIIII		
XIIIIIIIIIIII	.//////	//////					///////	///////	AIIIIIIIIIII	
+++++++++++++++++++++++++++++++++++++++	HHH	HHH	++++++	*******	19. Froposed D	epth 1	SA. Formation		20. Hotary or C.T.	
	//////		//////		2700'		San Andr	es	Rotary	
	hatherDh		121A Kind	& Status Plug. Bond	21B. Drilling C	ontractor		22. Approx	. Date Work will start	
21. Elevations (Show whether DF, RT, etc.)					1.	Collier Drilling Corp.		January 15, 1981		
3936.5	<u> </u>	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~		<u></u>			<u>, , , , , , , , , , , , , , , , , , , </u>			
23.			Р	ROPOSED CASING A	AND CEMENT PR	OGRAM				
					OT SETTING	DEPTU	SACKS OF		EST. TOP	
SIZE OF HO	LE	SIZE OF	CASING	WEIGHT PER FO	UT SETTING	DEFIN	SACKS OF			

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
10 3/4"	8 5/8"	24#	300'	150 Sxs.	Surface
7 7/8"	4 1/2"	10 1/2#	2700'	700 Sxs.	Surface
			·····		
			Į		1

Plan to test the San Andres formation. 8 5/8" casing will be run to approximately 300' and set with 150 Sxs. of Class C cement with 2% CaCl. Cement will be circulated to surface. Will drill out of the 8 5/8" casing with 7 7/8" bit to approximately 2700'. If sufficient shows are encountered will then run 2700' of 4 1/2" casing and set with 700 Sxs. of 50/50 poz mix 2% gel and 8# salt/sx. cement to surface. Will then log, perforate and complete well.

AFFROVAL VAND FOR 90 DAYS UNLESS DRILLING COMMENCED,

-7-81 FXPIRES

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE AND PROVED AND PROVED BY TITLE SUPERVISOR, DISTRICT II DATE JAN 0 7 1981

CONDITIONS OF APPROVAL, IF ANY: