

1	1	1
2	1	1
3	1	1
4	1	1
5	1	1
6	1	1
7	1	1
8	1	1
9	1	1
10	1	1

NEW MEXICO OIL CONSERVATION COMMISSION

C-107 and C-109
Effective 1-1-05

FEB 18 1981

O.C.D.

SUNDRY NOTICES AND REPORTS ON WELLS

ARTESIA OFFICE

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.

Oil Well ☒ Gas Well ☐ Other ☐

Name of Operator

SelCo, Inc. ✓

Address of Operator

P.O. Box 798, Artesia, New Mexico 88210

Location of Well

Section G 1980 FEET FROM THE North LINE AND 1980 FEET FROM

East LINE, SECTION 10 TOWNSHIP 9 S RANGE 28 E

15. Elevation (Show whether DF, RT, GR, etc.)

3936.5 GL

5a. Indicate Type of Lease

State ☐

Free ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name

Moonshine 10

9. Well No.

#1

10. Field and Pool, or Wildcat

Wildcat - San Andres

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SURSEQUENT REPORT OF:

COMMENCE DRILLING WORK ☐
REABANDON ☐
OR ALTER CASING ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☒
CASING TEST AND CEMENT JOE ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

While Drilling or Completion Operations, it is the duty of the operator to maintain accurate records, including estimated date of starting any operations.
(1) SEE RULE 1100.

January 16, 1981 - Commenced drilling operations. Spud well with 12 1/2" bit.
Ran 320' of 8 5/8", 24# casing. Cemented with 200 Sxs. Class C 2% CaCl₂.
Cement circulated to surface. WOC 18 hours. Pressured up 1000# for
30 minutes. Held O.K.

January 22, 1981 - T.D. 2698'. No discernable shows or breaks on Schlumberger Density Log.
Recommendation - Plug and Abandon well.

Set the following plugs:

First Plug:	2698' - 2600'	35 Sxs. Class C 2% CaCl ₂ cement.
Second Plug:	1900' - 1800'	35 Sxs. Class C 2% CaCl ₂ cement.
Third Plug:	900' - 800'	35 Sxs. Class C 2% CaCl ₂ cement.
Fourth Plug:	250' - 150'	35 Sxs. Class C 2% CaCl ₂ cement.
Top Plug:	-0-	15 Sxs. Class C 2% CaCl ₂ cement.

New Mexico Oil Conservation Division was notified prior to
plugging operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TITLE Agent

DATE 2/9/81

TITLE SUPERVISOR, DISTRICT II

DATE FEB 24 1981

REMARKS OF APPROVAL, IF ANY: