HO. OF COPIES RECEIVE	VED							10	Form C-103		
DISTRIBUTION								Supersedes Old C-102 and C-103			
ANTA FE		1		NE	M WEXICO OIL	. CONS	ERVATION COMMISSION		Effective 1-1	-65	•
ILE		4	<u>/</u>				BAR 1 6 1		5a. Indicate Typ		
'.s.g.s.							<sub>*</sub> ≠,	i	State X	· - · · - r	$\neg$
AND OFFICE							A market has a second	<u> </u>	5. State Oil 6 G	Fee.	
PERATOR							ARTEMA, OH	of Ged	LG - 6693	as Fadse No.	
									iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii	mmm	$\overline{n}$
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)											
OIL [	GAS	<u> </u>		•					7. Unit Agreeme	nt Name	
WELL	WELL	لكا		OTHER-					8. Form or Leas	e Name	
MESA PETROLEUM CO.									NED STATE	e 14410e	
Address of Operator									9. Well No.		
1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701									1		
Location of Well									10. Field and Pool, or Wildcat		
UNIT LETTER K 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FRO									WILDCAT		
ONLY CELLER TO		·									III
THE WES	ST L	INE. S	ECTIO	эн5	TOWNSHIP	98		ММРМ.			III
		<b>.</b> .									777
	IIII	III	III	15. E	Clevation (Show t	whether	DF, RT, GR, eic.)		12. County		111.
		III	777.	111111	3933	3.7' (	iR ·		CHAVES	1111111	777
•	1	Che	ck /	Appropriate I	Box To India	cate N	ature of Notice, Rep	ort or Othe	er Data		
<b>N</b>				ITENTION TO		1			REPORT OF	:	
								<del></del>		<b></b> ,	_
ERFORM REMEDIAL WO	AK [	]			PLUG AND ABAND	on 📮	REMEDIAL WORK		ALTE	RING CASING	
EMPORARILY ABANDON		]		•			COMMENCE DRILLING OPNS.	X	PLUS	AND ABANDONMENT	
ULL OR ALTER CASING		]			CHANGE PLANS		CASING TEST AND CEMENT J	os X			
· •	<b>3</b> , .						OTHER		<del></del>		لــا ـ
						_			in the second		
<del></del>		.\		(Closel	w state all parti		ils, and give pertinent date	s including	estimated date of	starting any prop	nsed
13 100 "C' 310 sx	3/8° 0 sx " +2° 0'. to 1	", 4 Thi % Ca Set oit.	8#, xse Cl. 3	H-40 casi t + 4% CaC Cement d plugs with	ing set at Cl, 300 sx did not cin 1 260 sx Th nessed by M	798' HLW f culat nixset M. Sti	81 and drilled to Cemented with 4% CaCl, and ta te. Ran temperat + 2 1/2 yds gra ubblefield of NMOC	350 sx Hl iled in v ure surve vel. Ci	_W + 4% Ca with 200 s ey - TOC @ rculated l	C1, x O	
XC 1 hereby certify tha	: NI it the is	MOCE nform	(3)	B), TLS, CE	EN RCDS, Al	he best (	ROSWELL, MEC, LA of my knowledge and belief.	•		CH 13, 1981	
					1111						
PROVED BY MA	he	, _[d	1/1	Mam	TIT	LE	l and gas inspector		DATE MA	R 1 7 1981	