

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

APR 28 1981

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>	
2. Name of Operator Fred Pool Drilling Co. ✓		7. Unit Agreement Name O. C. D.	
3. Address of Operator 1300 Clovis Star Rt., Roswell, N.M. 88201		8. Farm or Lease Name J C Nail	
4. Location of Well UNIT LETTER B 660 FEET FROM THE N LINE AND 1980 FEET FROM THE E LINE, SECTION 33 TOWNSHIP 5S RANGE 24 E N.M.P.M.		9. Well No. 2	
10. Field and Pool, or Wildcat Wildcat- Abo			
15. Elevation (Show whether DF, RT, GR, etc.) 4058.8 GL		12. County Chaves	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	8 5/8 casing <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Feb. 10, 1981

Set 1510 ft. new 2 1/4" 8 5/8 casing. Used 600 sx 65/35 Poz with D-20 Bentonite, D-44 Slat, and D-42 Kolite with 2% SI, calcium chloride; Class C cement. Cement did not circulate. Ran temperature survey; showed top of cement at 400 ft. from surface.

Feb. 11, 1981

One inch cement to surface, with Dowell truck. Used 625 sx Class C cement with 2% Calcium Chloride, and no additives.

W O C 2 1/2 hrs. Ran pressure test to 500# for thirty minutes, no pressure drop.

Commenced drilling operations. 2-13-81

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Renta Pool TITLE Secretary DATE Feb. 18, 1981

APPROVED BY Mike Williams TITLE OIL AND GAS INSPECTOR DATE APR 28 1981

CONDITIONS OF APPROVAL, IF ANY: